

SONALIKA

— THE TOUGHEST —
PERFORMER
« FOR YOUR FIELD »

75



AGILE 4 CYLINDER
ENGINE

12F+12R SYNCHROMESH
TRANSMISSION

HEAVY LIFT
CAPACITY

PARALLELOGRAM
LOADER OPTION

INTEGRATED SAFETY
HVAC CABIN (OPTIONAL)



**COST
EFFICIENT**
MECHANICAL TRACTORS

MADE OF
**REAL
STEEL**

STRATEGIC
COLLABORATION
WITH
YANMAR

**THE TOUGHEST
PERFORMER
«FOR YOUR FIELD»**

S75

SONALIKA



FEATURES	S 75
Model Description	SONALIKA 75
ENGINE	
Engine Type	4 Cylinder Turbo Charged Engine
HP Category	75
No. of Cylinders	4
Aspiration	Turbo Charged
Cubic Capacity (cc)	3707
Rated RPM	2200
Air Cleaner	Dry Air Cleaner with Clogging Sensor
Cold Start	Standard
Max Torque (nm) (+/- 5%)	278@1200 ERPM
Exhaust	Underhood Downdraft Silencer Underhood Upward
TRANSMISSION	
Drive	4WD
Clutch	Double Clutch
Gearbox	12F+12R
Transmission	Synchronmesh
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	33.73 @ 2200
Minimum Speed (Km/Hr)	1.69 @ 2200
BRAKES	
Brakes	Oil Immersed Brakes
Type of Actuation	Mechanical
Parking Brake	Independent Type
DIFFERENTIAL LOCK	
Differential Lock	Standard, Foot Operated
PTO	
PTO (RPM)	540/540E
PTO (Actuation)	Mechanical
STEERING	
Steering	Power
ELECTRICAL	
Battery	12V, 88 AH or 110 AH
Alternator	12V, 90Amps
Seven Pin Trailer Socket	Standard
HYDRAULICS	
3 Point Linkage	CAT-II
Stay Bars	Adjustable
Hydraulic Lifting Capacity	2500Kg (3000Kg Optional)
Auxiliary Hydraulic Circuit	2DA/2SA
Lift Rods	Standard

FEATURES	S 75
SAFETY SWITCH	
Clutch Safety Switch	Standard
PTO Safety Switch	Standard
Neutral Safety Switch	Standard
CAPACITY (LTRS)(+/-5%)	
Fuel Tank (Ltr)	64
TURNING RADIUS	
Without Brakes (m)	LHS: 6.9 , RHS: 6.53
TYRE	
Front	11.2 - 24
Rear	16.9-30
DIMENSIONS & WEIGHT(+/-5%)	
Weight (Kg)	3180
Wheel Base (mm)	2350
Total Length (mm)	4330
Total Width (mm)	1910
Height (mm) up to ROPS	2775
Min. Ground Clearance (mm)	385
Front Track (mm)	1615-1910
Rear Track (mm)	1515-1805
OTHERS	
Fuel Indicator Gauge	Standard
Front Tow Hook	Standard, Inbuilt in front weight
Front & Rear Weights with Std. Ballast	Front- 30KgX2 and 24KgX4 Rear- 2X30 Kg
Trailer Hitch	Swinging Drawbar
ROPS	Standard
OPTIONAL FEATURES	
Cabin	HVAC/Heater (Optional)
Front Mudguard	Standard
Trailer Brake	HTB/ATB
Tyre	Front: 12.4X24, Rear: 18.4X30 Rear Optional: 13.6X38
2WD	Front: 7.5X16, Rear 16.9X30
Radial	280/85R24, 420/85R30

*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE, please correlate with latest updates. Accessories shown may not be part of standard product.

DEALER STAMP



SONALIKA S75 12+12 AF

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91 1882 302220, 302221

Fax: +91 1882 302293 | Email: exports@sonalika.com | URL: www.sonalika.com/www.solisworld.com